

Front View



Rear View

### **RTI Control System**



# VHX-4

#### 4 x 4 HDMI 2.0 Matrix Switcher

The VHX-4 is a 4K 4x4 Matrix Switcher for professional distribution of up to four HDMI 2.0 video sources to four displays.

The VHX-4 enables cross-point switching from any input to any output, and supports 4K@60Hz 3D signals. It features 18Gbps bandwidth and HDCP 2.2 on all inputs and outputs. The unit is fully compliant with the HDMI 2.0 standard and backward compatible with HDMI 1.4 sources and displays. Four S/PDIF ports allow breakout audio from corresponding HDMI outputs.

The VHX-4 has multiple control options including RS-232, TCP/IP, Web GUI or via the front panel buttons.

### **Key Features**

- Provides routing of up to 4 video sources to 4 displays / projectors.
- HDCP 2.2 compliant and support for HDMI 2.0.
- 3D compatible.
- Four S/PDIF ports provide de-embedded HDMI audio output.
- Powerful EDID management.
- LCD shows real-time I/O connection status.
- Supports multiple control methods, including front panel, RS232, TCP/IP and Web GUI.
- Easy installation with rack-mount design.



## **Specifications**

Power Supply	+24 VDC, 1.25A
Mounting	Rack mount 1 RU or free standing
Dimensions WxHxD	17.2" (437mm) x 1.73" (44mm) x 9.31" (236.5mm)
Weight	
Operating Temperature	C -10 to +40 degrees F +14 to +104 degrees
Operating Humidity	5% to 95% Non-condensing
Digital Video Input	Four HDMI
Digital Video Output	Four HDMI
Compliance	HDMI 2.0, HDCP 2.2
Resolution Range	640x480@60Hz to 4K@60Hz 4:4:4, 1080p 3D

EDID Management	Built-in EDID data and manual EDID management
Digital Audio Output	Four S/PDIF for de-embedded HDMI audio
Supported Audio Formats	Dolby Digital, DTS, DTS-HD
RS-232 Control Port	One, Bi-directional (3-pin Phoenix Connector)
Ethernet Control Port	One, 10/100Base-T (RJ45)
Front Panel Control	8 Buttons
USB	Micro USB for Firmware Update
Warranty	Three Years (Parts & Labor)

All features and specifications subject to change without notice

